



Cyl-Tec's automated acetone filling system ensures that our acetylene cylinders are processed correctly, with the shortest lead times.

ACETYLENE CYLINDERS

Cyl-Tec's acetylene cylinders are completely asbestos-free and filled with a high quality glass fiber reinforced calcium silicate porous mass.

MODEL*	ACETYLENE CAPACITY* ft ³ (m ³)	ACETYLENE CAPACITY* pounds (kg)	INTERNAL VOLUME in ³ (liters)	DIAMETER (I.D.) in (mm)	HEIGHT WITH CAP in (mm)	ACETONE pounds (kg)	TARE WEIGHT WITHOUT CAP pounds (kg)	SHIPPING WEIGHT pounds (kg)
10 (MC)	10 (0.28)	0.68 (0.31)	122 (2.0)	3.81 (97)	15.40 (391)	1.3 (0.59)	7.68 (3.48)	7.64 (3.47)
40 B - Standard)	40 (1.13)	2.72 (1.23)	470 (7.7)	6.0 (152)	23.20 (589)	5.1 (2.31)	23.8 (10.77)	23.62 (10.71)
40 (B - Big Flange)*	40 (1.13)	2.72 (1.23)	470 (7.7)	6.0 (152)	25.75 (654)	5.1 (2.31)	27.9 (12.63)	29.87 (13.55)
75	75 (2.12)	5.10 (2.31)	855 (14.0)	7.0 (178)	30.75 (781)	9.3 (4.22)	43.3 (19.64)	45.22 (20.51)
145	145 (4.11)	9.68 (4.39)	1538 (25.2)	8.0 (203)	39.50 (1003)	17.9 (8.12)	75.5 (34.25)	77.20 (35.02)
250	250 (7.08)	17.01 (7.72)	2652 (43.5)	10.0 (254)	43.25 (1099)	30.8 (13.97)	117.5 (53.30)	118.88 (53.92)

Cylinders are DOT-8AL/TC-8WAM except 40 ft³ (B - Big Flange)* is DOT-8AL only

*At 250 psig and 70°F (17.2 barg and 21°C)