



Aluminum Beverage CO₂ cylinders are preferred due to their light weight and corrosion resistance.

BEVERAGE CO₂ ALUMINUM CYLINDERS

Include a bare brushed finish and CGA 320 CO₂ valves as standard. 20# and #50 CO₂ cylinders include a heavy duty reinforced nylon carry handle.

ALUMINUM CO ₂ CYLINDER	CARBON DIOXIDE (CO ₂) POUNDS (KG)	SERVICE PRESSURE	OUTSIDE DIAMETER	LENGTH	WEIGHT	NITROGEN (N ₂) ft ³ at 70 F (Liters at 20 C)	INLET THREAD
Model	at 68% fill	psig (bar)	inches (mm)	inches (mm)	pounds (kg)		
1.5# CO ₂	1.5 (0.68)	1800 (124)	3.2 (82)	11.5 (292)	1.8 (0.83)	4.3 (121.76)	3/4"-16 UNF-2B
2.5# CO ₂	2.5 (1.14)	1800 (124)	4.4 (111)	11.0 (280)	3.7 (1.66)	7.2 (203.88)	3/4"-16 UNF-2B
5# CO ₂	5.0 (2.27)	1800 (124)	5.3 (133)	14.2 (362)	7.5 (3.42)	14.5 (410.59)	1-1/8"-12 UNF-2B
10# CO ₂	10 (4.55)	1800 (124)	6.9 (175)	16.6 (422)	14.1 (6.40)	29.0 (821.19)	1-1/8"-12 UNF-2B
15# CO ₂	15 (6.82)	1800 (124)	6.9 (175)	23.2 (589)	17.0 (7.71)	43.3 (1226.12)	1-1/8"-12 UNF-2B
20# CO ₂	20 (9.09)	1800 (124)	8.0 (203)	23.3 (592)	24.8 (11.2)	57.6 (1631.05)	1-1/8"-12 UNF-2B
50# CO ₂	50 (22.7)	1800 (124)	8.6 (218)	46.3 (1177)	48.8 (22.1)	144.0 (4077.63)	1-1/8"-12 UNF-2B