



Cyl-Tec's Aluminum Medical Cylinders are light-weight and corrosion-resistant.

## ALUMINUM MEDICAL CYLINDERS

Cyl-Tec's Aluminum Medical Cylinders are made of alloy 6061-T6 aluminum and includes a painted shoulder and clear coat.

MODEL	Oxygen Capacity	Service Pressure	Diameter	Height	Weight	Water Volume	Inlet Thread
	<i>ft<sup>3</sup> at 70°F (m<sup>3</sup> at 21°C)</i>	<i>psig (bar)</i>	<i>in. (mm)</i>	<i>in. (mm)</i>	<i>lb. (kg)</i>	<i>in<sup>3</sup> (liters)</i>	
<b>Med B (M-6)</b>	6.0 (.17)	2216 (153)	3.2 (81)	11.8 (300)	2.2 (1.0)	63 (1.0)	3/4"-16 UNF-2B
<b>Med C (M-9)</b>	9.0 (.25)	2015 (139)	4.4 (111)	11.0 (279)	3.6 (1.6)	106 (1.7)	3/4"-16 UNF-2B
<b>Med D</b>	14.5 (.40)	2015 (139)	4.4 (111)	16.5 (419)	5.1 (2.3)	170 (2.8)	3/4"-16 UNF-2B
<b>Med E</b>	23.7 (.67)	2015 (139)	4.4 (111)	25.0 (635)	7.4 (3.4)	278 (4.6)	3/4"-16 UNF-2B
<b>M-22</b>	22.0 (.62)	2216 (153)	5.3 (135)	17.2 (436)	9.3 (4.2)	236 (3.9)	1-1/8"-12 UNF 2B
<b>M-33</b>	33.0 (.93)	2216 (153)	6.9 (175)	16.0 (406)	14.2 (6.4)	355 (5.8)	1-1/8"-12 UNF 2B
<b>M-60</b>	60.1 (1.70)	2216 (153)	7.3 (185)	22.9 (582)	22.3 (10.1)	642 (10.5)	1-1/8"-12 UNF 2B
<b>M-90</b>	87.4 (2.47)	2216 (153)	7.3 (185)	32.7 (831)	30.0 (13.6)	933 (15.3)	1-1/8"-12 UNF 2B
<b>M-150</b>	153.2 (4.34)	2015 (139)	8.0 (203)	47.9 (1,217)	48.5 (22.0)	1800 (29.5)	1-1/8"-12 UNF 2B
<b>M-265</b>	265.0 (7.50)	2216 (153)	9.8 (250)	51.4 (1,305)	87.0 (39.5)	2831 (46.4)	1-1/8"-12 UNF 2B



### OXY-TRU® MEDICAL GAS VALVE

Give your cylinder fill plant personnel a quick visual confirmation on the valve's position (open or closed) by simply looking down the fill manifold line.

