



Cyl-Tec's Aluminum CO₂ Cylinders — specially designed for the beverage carbonation industry — are light-weight and corrosion-resistant.

ALUMINUM CO₂ CYLINDERS

Cyl-Tec's Aluminum CO₂ Cylinders have a bare-brushed finish and CGA 320 CO₂ valves as standard. All 10 lb, 20 lb, and 50 lb cylinders include a heavy-duty, reinforced nylon carry handle. Manufactured to DOT-3AL and ISO 7866 specifications.

MODEL	Carbon Dioxide (CO ₂)	Service Pressure	Diameter	Height	Tare Weight	Water Volume	Nitrogen (N ₂)	Inlet Thread
	lb. (kg) at 68% fill	psig (bar)	in. (mm)	in. (mm)	lb. (kg)	in ³ (liters)	ft ³ at 70°F (m ³ at 21°C)	
1.5 lb	1.5 (0.68)	1,800 (124)	3.2 (82)	11.5 (292)	3.5 (1.6)*	61 (1.0)	4.3 (121.76)	3/4"-16 UNF-2B
2.5 lb	2.5 (1.14)	1,800 (124)	4.4 (111)	11.0 (280)	4.6 (2.1)*	98 (1.6)	7.2 (203.88)	3/4"-16 UNF-2B
5 lb	5.0 (2.27)	1,800 (124)	5.3 (133)	14.2 (362)	8.1 (3.7)*	208 (3.4)	14.5 (410.59)	1-1/8"-12 UNF-2B
10 lb	10 (4.55)	1,800 (124)	6.9 (175)	16.6 (422)	16.3 (7.4)**	409 (6.7)	29.0 (821.19)	1-1/8"-12 UNF-2B
20 lb	20 (9.09)	1,800 (124)	8.0 (203)	23.3 (592)	26.4 (12.0)**	818 (13.4)	57.6 (1,631.05)	1-1/8"-12 UNF-2B
50 lb	50 (22.7)	1,800 (124)	8.6 (218)	46.3 (1,177)	53.8 (24.4)**	2038 (33.4)	144.0 (4,077.63)	1-1/8"-12 UNF-2B

* Tare weight includes valve

** Tare weight includes valve & carry handle

One Resource. Zero Headaches.®

Your one resource for gas cylinders, cryogenic vessels, small & large bulk tanks, valves, and cryo repair services.

(Customers outside U.S. call +1-630-844-8800.)

U.S. TOLL FREE **888-429-5832**

www.cyl-tec.com

