



Cyl-Tec's Aluminum Medical Cylinders are light-weight and corrosion-resistant.

ALUMINUM MEDICAL CYLINDERS

Cyl-Tec's Aluminum Medical Cylinders are made of alloy 6061-T6 aluminum and includes a painted shoulder and clear coat. Also manufactured to DOT-3AL and ISO 7866 specifications.

MODEL	Oxygen Capacity	Service Pressure	Diameter	Height	Weight	Water Volume	Inlet Thread
	ft ³ at 70°F (m ³ at 21°C)	psig (bar)	in. (mm)	in. (mm)	lb. (kg)	in ³ (liters)	
Med B (M-6)	6.0 (.17)	2,216 (153)	3.2 (81)	11.8 (300)	2.2 (1.0)	63 (1.0)	3/4"-16 UNF-2B
Med C (M-9)	9.0 (.25)	2,015 (139)	4.4 (111)	11.0 (279)	3.6 (1.6)	106 (1.7)	3/4"-16 UNF-2B
Med D	14.5 (.40)	2,015 (139)	4.4 (111)	16.7 (423)	5.5 (2.5)	170 (2.8)	3/4"-16 UNF-2B
Med E	23.7 (.67)	2,015 (139)	4.4 (111)	25.6 (651)	7.8 (3.5)	278 (4.6)	3/4"-16 UNF-2B
M-22	22.0 (.62)	2,216 (153)	5.3 (133)	16.7 (425)	9.3 (4.2)	236 (3.9)	1-1/8"-12 UNF 2B
M-33	33.0 (.93)	2,216 (153)	6.9 (175)	16.0 (406)	14.7 (6.7)	360 (5.9)	1-1/8"-12 UNF 2B
M-60	60.1 (1.70)	2,216 (153)	7.3 (185)	22.9 (582)	22.8 (10.3)	610 (10.0)	1-1/8"-12 UNF 2B
M-90	87.4 (2.47)	2,216 (153)	7.3 (185)	32.7 (831)	30.0 (13.6)	928 (15.2)	1-1/8"-12 UNF 2B
M-150	153.2 (4.34)	2,015 (139)	8.0 (203)	48.2 (1,223)	51.6 (23.4)	1,800 (29.5)	1-1/8"-12 UNF 2B
M-265	265.0 (7.50)	2,216 (153)	9.8 (250)	50.9 (1,293)	87.1 (39.5)	2,831 (46.4)	1-1/8"-12 UNF 2B



OXY-TRU® MEDICAL GAS VALVE

Give your cylinder fill plant personnel a quick visual confirmation on the valve's position (open or closed) by simply looking down the fill manifold line. Available in CGA 870, CGA 940, & CGA 950 models.

